

PATENT
Attorney Docket No. GNA7005152001

AMENDMENTS TO THE CLAIMS

Please cancel claims 19-22 without prejudice to pursue these claims in a related application, amend claims 1 and 16, and insert new claims 23-26, as follows:

1. (Currently Amended) A method of saving data within a persistent data space of a hearing aid, the method comprising the steps of:
processing an input signal by a processor according to a predetermined algorithm to generate a processed output signal,
~~generating a plurality of a first data sets set, representing respective a value or values of one or several predetermined~~ hearing aid associated variable(s), by the processor,
~~writing the plurality of first data sets set to a respective storage areas within the persistent data space,~~
generating a second data set, representing an updated value or values of the one or several hearing aid associated variable(s), by the processor.
writing the second data set to a different respective storage area within the persistent data space, and
~~indicating a valid data set, one of the plurality of first and second data sets as a valid data set,~~ by setting a value of at least one data variable in the persistent data space.
2. (Original) A method according to claim 1, wherein the processor reads the value of the at least one data variable during power on of the hearing aid to identify and load the valid data set of the plurality of data sets.
3. (Original) A method according to claim 1, wherein the plurality of data sets are written to their respective storage areas in an intermittent manner.
4. (Original) A method according to claim 1, wherein the plurality of data sets are written to the persistent data space during normal operation of the hearing aid.

PATENT

Attorney Docket No. GNA7005152001

5. (Original) A method according to claim 1, wherein the plurality of data sets comprise respective data representing accumulated utilisation time values of the hearing aid.
6. (Original) A method according to claim 1, wherein the plurality of data sets comprise respective data representing values of signal processing parameters of the predetermined algorithm.
7. (Original) A method according to claim 1, wherein the persistent data space is arranged in one or several memory device(s) selected from the group consisting of: (EEPROM, EPROM, Flash Memory, RAM powered by a back-up voltage).
8. (Original) A method according to claim 7, wherein persistent data space is arranged in a single external EEPROM device and each data set of the plurality of data sets is placed in a separate memory-page of the external EEPROM.
9. (Original) A method according to claim 1, wherein each data set of the plurality of data sets is written to the persistent data space at regular time intervals, the time interval being between 5 minutes and 60 minutes.
10. (Original) A method according to claim 1, wherein the at least one data variable is stored within the persistent data space in a storage area separate from the respective storage areas of the plurality of data sets.
11. (Original) A method according to claim 1, wherein each data set comprises a data variable indicating whether that data set is the valid data set.
12. (Original) A method according to claim 11, wherein the data variables of the plurality of data sets are represented by respective counter values.

PATENT

Attorney Docket No. GNA7005152001

13. (Original) A method according to claim 1, wherein each data set of the plurality of data sets is associated with an error detection or error correction code within the persistent data space.

14. (Original) A method according to claim 1, wherein the plurality of data sets are constituted by a first and a second data set, and

the at least one data variable comprises a single binary data variable indicating the valid data set.

15. (Original) A hearing aid comprising a persistent data space and a processor adapted to perform a method of saving data according to claim 1.

16. (Currently Amended) A hearing aid adapted to store values of hearing associated variables in a persistent memory device during normal use of said hearing aid, the hearing aid comprising:

an input signal channel providing an input signal,

a processor adapted to:

process the input signal according to a predetermined algorithm to generate a processed output signal,

generate a first data set representing a value or values of one or several ~~predetermined~~ hearing aid associated variable(s),

writing the first data set to a first memory segment within the persistent memory device,

generating a second data set representing ~~a value~~ an updated value or values of the one or several ~~predetermined~~ hearing aid associated variable(s),

writing the second data set to a second memory segment within the persistent memory device,

selectively indicating the first or the second data set as a valid data set by setting a data variable value in a third memory segment in the persistent memory device.

17. (Original) A hearing aid according to claim 16, wherein the persistent memory device is a serial EEPROM.

PATENT
Attorney Docket No. GNA7005152001

18. (Original) A hearing aid according to claim 17, wherein each of first, second and third memory segments is placed in a separate memory-page of the serial EEPROM.

19-22. (Canceled)

23. (New) A method according to claim 1, wherein one of the value or values associated with the first data set, and one of the updated value or values associated with the second data set, correspond to a same parameter.

24. (New) A method according to claim 23, wherein the parameter is selected from the group consisting of a preset switch operation, a volume control operation, and a variable for use in a signal processing algorithm.

25. (New) A hearing aid according to claim 16, wherein one of the value or values associated with the first data set, and one of the updated value or values associated with the second data set, correspond to a same parameter.

26. (New) A hearing aid according to claim 25, wherein the parameter is selected from the group consisting of a preset switch operation, a volume control operation, and a variable for use in a signal processing algorithm.